

JAKE/JILL LED

165

Fixture

Stand Alone/Continuous Run

Fixture Lengths	TR
Fixture Type	Approval

Continuous Run Segments

TR - Trim

Г			
	Starter	Middle	End
L			

Stand Alone Overall Length



Overall	Rough In
Length (in)	Length (in)
25.750"	25.125"
37.750"	37.125"
49.750"	49.125"
61.750"	61.125"
73.750"	73.125"
85.813"	85.188"
97.813"	97.188"
	Length (in) 25.750" 37.750" 49.750" 61.750" 73.750" 85.813"

Continuous Run Lengths, Rough In Lengths and Fixture Length Segments


TR

Nomir Length		Rough In Length (in)	Fixture Length Segments
9	9' - 1.813"	9' - 1.188"	6-3
10	10' - 1.813"	10' - 1.188"	8-2
11	11' - 1.813"	11' - 1.188"	8-3
12	12' - 1.813"	12' - 1.188''	8-4
13	13' - 1.813"	13' - 1.188"	8-5
14	14' - 1.813"	14' - 1.188''	8-6
15	15' - 1.813"	15' - 1.188"	8-7
16	16' - 1.813"	16' - 1.188"	8-8
17	17' - 1.875"	17' - 1.250''	8-6-3
18	18' - 1.875"	18' - 1.250''	8-8-2
19	19' - 1.875"	19' - 1.250''	8-8-3
20	20' - 1.875"	20' - 1.250''	8-8-4
21	21' - 1.875"	21' - 1.250"	8-8-5
22	22' - 1.875"	22' - 1.250''	8-8-6

Nomir Lengtl			Rough In Length (in)	Length Segments
23	23' - 1.8	375''	23' - 1.250"	8-8-7
24	24' - 1.8	375''	24' - 1.250''	8-8-8
25	25' - 1.9	38"	25' - 1.313"	8-8-6-3
26	26' - 1.9	38"	26' - 1.313"	8-8-8-2
27	27' - 1.9	38"	27' - 1.313''	8-8-8-3
28	28' - 1.9	38"	28' - 1.313"	8-8-8-4
29	29' - 1.9	38"	29' - 1.313"	8-8-8-5
30	30' - 1.9	38"	30' - 1.313''	8-8-8-6
31	31' - 1.9	38"	31' - 1.313"	8-8-8-7
32	32' - 2.0	000''	32' - 1.375"	8-8-8-8
33	33' - 2.0	000''	33' - 1.375"	8-8-8-6-3
34	34' - 2.0	000''	34' - 1.375"	8-8-8-8-2
35	35' - 2.0	000''	35' - 1.375"	8-8-8-3
36	36' - 2.0	000"	36' - 1.375"	8-8-8-4

Nomir Length		Rough In Length (in)	Fixture Length Segments
37	37' - 2.000''	37' - 1.375''	8-8-8-8-
38	38' - 2.000''	38' - 1.375''	8-8-8-8-
39	39' - 2.063''	39' - 1.438''	8-8-8-8-7
40	40' - 2.063''	40' - 1.438''	8-8-8-8-8
41	41' - 2.063"	41' - 1.438''	8-8-8-8-6-3
42	42' - 2.063''	42' - 1.438''	8-8-8-8-8-2
43	43' - 2.063''	43' - 1.438''	8-8-8-8-8-
44	44' - 2.063''	44' - 1.438''	8-8-8-8-8-
45	45' - 2.125''	45' - 1.500''	8-8-8-8-8-
46	46' - 2.125''	46' - 1.500''	8-8-8-8-8
47	47' - 2.125''	47' - 1.500''	8-8-8-8-8-7
48	48' - 2.125''	48' - 1.500''	8-8-8-8-8-8
49	49' - 2.125''	49' - 1.500''	8-8-8-8-6-3
50	50' - 2.125"	50' - 1.500''	8-8-8-8-8-8-2

Rough In Length: Trim (TR) = O.A.L - 0.625 **Rough In Width:** 165 = 2.500"



#825-00030 V-1113