



COLLIN LED 325



10 DAYS
200' total

SPECIFICATION CODE

COL-LED-325-QS

model configuration direct light engine indirect light engine color length finish lens voltage driver mounting

CSS selection options only²

standard cable length standard cord color standard canopy standard canopy finish

Model	Configuration	Direct Light Engine	Indirect Light Engine	Color Temp	Nominal Length	Finish	Lens	Voltage	Driver	Mounting	CSS Options ²
COL-LED-325-QS 3.25" profile	1DR-11N - 1 lamp direct/ 1 indirect	SLO - Standard Lumen Output	SLO - Standard Lumen Output	30 - 3000K	4 - 4'	Anodized	FW	120	EB - Electronic (standard)	CSS - Cable Suspended (36" standard)	Orientation Cable Length Cord Color Canopy Canopy Finish
		HLO - High Lumen Output	HLO - High Lumen Output	35 - 3500K 40 - 4000K	8 - 8'	SC - Satin Clear		277			
	1DR-01N - 1 lamp direct/ 0 indirect	CLO ¹ - Custom Lumen Output	CLO ¹ - Custom Lumen Output		Continuous Run	Powder Coat			Dimming 0-10V		
					CR12 - 12' CR16 - 16' CR20 - 20' CR24 - 24'	MW - Matte White FB - Flat Black			D1 - 1% (nom) D10 - 10%	WM - Wall Mount	
									HLA2 ³ - Lutron 2 wire HLA3 - Lutron 3 wire HLH - Lutron H series		

• (0) designates
No lamp option

1 refer to CLO Calculator below for code selection
2 see CSS options below for selections
3 120V only

[CLO Calculator](#)



CSS Options

Cable Length

36 - 36" (standard)
72 - 72"
120 - 120"

Power Cord Color

W - White
B - Black
G - Gray (standard)

Canopy

STND - Bracket bar w/5" round canopy
NC - No canopy 1/4-20 side exit cable gripper
(1/4-20 stud provided by others)

Canopy Finish

MW - Matte White
SMT - Silver Matte Texture
FB - Flat Black

Dimensions

