



NOLAN LED 325



10 DAYS
400' total

SPECIFICATION CODE

NOL-LED-325-QS

model light engine color temp length finish lens voltage driver mounting

CSS selection options only²

standard cable length	standard cord color	standard canopy	standard canopy finish
-----------------------	---------------------	-----------------	------------------------

Model	Light Engine	Color Temp	Nominal Length	Finish	Lens	Voltage	Driver	Mounting	CSS Options ²
NOL-LED-325-QS 3.25" profile	SLO - Standard Lumen Output HLO - High Lumen Output CLO ¹ - Custom Lumen Output	30 - 3000K 35 - 3500K 40 - 4000K	4 - 4' 8 - 8' Continuous Run CR12 - 12' CR16 - 16' CR20 - 20' CR24 - 24'	Anodized SC - Satin Clear Powder Coat MW - Matte White FB - Flat Black	FW	120 277	EB - Electronic (standard) Dimming 0-10V D1 - 1% (nom) D10 - 10% HLA2 ³ - Lutron 2 wire HLA3 - Lutron 3 wire HLH - Lutron H series	CSS-DR - Cable Suspended (36" standard) SM - Surface Mount	CSS Orientation Cable Length Cord Color Canopy Canopy Finish

1 refer to CLO Calculator below for code selection
2 see CSS options below for selections
3 120V only

[CLO Calculator](#)



CSS Options

Cable Length 36 - 36" (standard) 72 - 72" 120 - 120"	Power Cord Color W - White B - Black G - Gray (standard)	Canopy STND - Bracket bar w/5" round canopy NC - No canopy 1/4-20 side exit cable gripper (1/4-20 stud provided by others)	Canopy Finish MW - Matte White SMT - Silver Matte Texture FB - Flat Black
--	---	---	--

Dimensions

