

**Fixture Lengths**


**TL**

Fixture Type

Approval

**Continuous Run Segments**

TL - Mud-over Flange



**Stand Alone Overall Length**



Fixture Length	Overall Length (in)	Rough In Length (in)
2'	25.640"	23.375"
3'	36.640"	34.375"
4'	47.640"	45.375"
5'	58.640"	56.375"
6'	70.080"	67.750"
7'	81.080"	78.750"
8'	91.080"	89.750"


**Continuous Run Lengths, Rough In Lengths and Fixture Length Segments**

Nominal Length (ft)	TL Overall Length (in)	Rough In Length (in)	Fixture Length Segments
9	9' - 6.080"	9' - 3.750"	5-5
10	10' - 5.520"	10' - 3.250"	8-3
11	11' - 4.520"	11' - 2.250"	8-4
12	12' - 3.520"	12' - 1.250"	8-5
13	13' - 2.960"	13' - 0.625"	8-6
14	14' - 1.960"	13' - 11.625"	8-7
15	15' - 0.960"	14' - 10.625"	8-8
16	16' - 0.400"	15' - 10.125"	8-6-3
17	16' - 11.400"	16' - 9.125"	8-8-2
18	17' - 10.400"	17' - 8.125"	8-8-3
19	18' - 9.400"	18' - 7.125"	8-8-4
20	19' - 8.400"	19' - 6.125"	8-8-5
21	20' - 7.840"	20' - 5.500"	8-8-6
22	21' - 6.840"	21' - 4.500"	8-8-7

Nominal Length (ft)	TL Overall Length (in)	Rough In Length (in)	Fixture Length Segments
23	22' - 5.840"	22' - 3.500"	8-8-8
24	24' - 4.280"	24' - 2.000"	8-8-6-4
25	25' - 3.280"	25' - 1.000"	8-8-8-3
26	26' - 2.280"	25' - 12.000"	8-8-8-4
27	27' - 1.280"	26' - 11.000"	8-8-8-5
28	28' - 0.720"	27' - 10.375"	8-8-8-6
29	28' - 11.720"	28' - 9.375"	8-8-8-7
30	29' - 10.720"	29' - 8.375"	8-8-8-8
31	30' - 10.160"	30' - 7.875"	8-8-8-6-3
32	31' - 9.160"	31' - 6.875"	8-8-8-8-2
33	32' - 8.160"	32' - 5.875"	8-8-8-8-3
34	33' - 7.160"	33' - 4.875"	8-8-8-8-4
35	34' - 6.160"	34' - 3.875"	8-8-8-8-5
36	36' - 4.600"	36' - 2.250"	8-8-8-8-7

Nominal Length (ft)	TL Overall Length (in)	Rough In Length (in)	Fixture Length Segments
37	37' - 3.600"	37' - 1.250"	8-8-8-8-8
38	38' - 3.040"	38' - 0.750"	8-8-8-8-6-3
39	39' - 2.040"	38' - 11.750"	8-8-8-8-8-2
40	40' - 1.040"	39' - 10.750"	8-8-8-8-8-3
41	41' - 0.040"	40' - 9.750"	8-8-8-8-8-4
42	41' - 11.040"	41' - 8.750"	8-8-8-8-8-5
43	42' - 10.480"	42' - 8.125"	8-8-8-8-8-6
44	43' - 9.480"	43' - 7.125"	8-8-8-8-8-7
45	44' - 8.480"	44' - 6.125"	8-8-8-8-8-8
46	45' - 7.920"	45' - 5.625"	8-8-8-8-8-6-3
47	46' - 6.920"	46' - 4.625"	8-8-8-8-8-8-2
48	48' - 4.920"	48' - 2.625"	8-8-8-8-8-8-4
49	49' - 3.920"	49' - 1.625"	8-8-8-8-8-8-5
50	50' - 3.360"	50' - 1.000"	8-8-8-8-8-8-6

Rough In Width:  
4.500"



#825-00142  
V-0616