


Fixture Lengths

CSS-R | RAS


Fixture Type

Approval

Continuous Run Individual Cable Centers



Stand Alone Cable Centers & Overall Length



Fixture Length	Cable/Arm Centers (in)	Fixture Length	Cable/Arm Centers (in)	Fixture Length	Cable/Arm Centers (in)
2'	26.000"	2'	26.000"	2'	26.000"
3'	38.000"	3'	38.000"	3'	38.000"
4'	50.000"	4'	50.000"	4'	50.000"

Fixture Length	Cable/Arm Centers (in)	Overall Length (in)
2'	26.000"	27.125"
3'	38.000"	39.125"
4'	50.000"	51.125"
6'*	74.000"	75.125"
7'*	86.000"	87.125"
8'*	98.000"	99.125"

* (2) power drops on dimming and PRS ballasts

Continuous Run Lengths and Fixture Length Segments


Nominal Length (ft)	CSS-R/RAS Overall Length (in)	Fixture Length Segments
6	6' - 5.125"	3-3
7	7' - 5.125"	4-3
8	8' - 5.125"	4-4
9	8' - 7.125"	3-3-2
10	9' - 7.125"	3-3-3
11	10' - 7.125"	4-3-3
12	11' - 7.125"	4-4-3
13	12' - 7.125"	4-4-4
14	13' - 9.125"	4-3-3-3
15	14' - 9.125"	4-4-3-3
16	15' - 9.125"	4-4-4-3
17	16' - 9.125"	4-4-4-4
18	17' - 11.125"	4-4-3-3-3
19	18' - 11.125"	4-4-4-3-3
20	19' - 11.125"	4-4-4-4-3

Nominal Length (ft)	CSS-R/RAS Overall Length (in)	Fixture Length Segments
21	20' - 11.125"	4-4-4-4-4
22	22' - 1.125"	4-4-4-3-3-3
23	23' - 1.125"	4-4-4-4-3-3
24	24' - 1.125"	4-4-4-4-4-3
25	25' - 1.125"	4-4-4-4-4-4
26	26' - 3.125"	4-4-4-4-3-3-3
27	27' - 3.125"	4-4-4-4-4-3-3
28	28' - 3.125"	4-4-4-4-4-4-3
29	29' - 3.125"	4-4-4-4-4-4-4
30	30' - 5.125"	4-4-4-4-4-3-3-3
31	31' - 5.125"	4-4-4-4-4-4-3-3
32	32' - 5.125"	4-4-4-4-4-4-4-3
33	33' - 5.125"	4-4-4-4-4-4-4-4
34	34' - 7.125"	4-4-4-4-4-4-3-3-3
35	35' - 7.125"	4-4-4-4-4-4-4-3-3

Nominal Length (ft)	CSS-R/RAS Overall Length (in)	Fixture Length Segments
36	35' - 9.125"	4-4-4-4-3-3-3-3-3-3
37	36' - 7.125"	4-4-4-4-4-4-4-4-3
38	37' - 7.125"	4-4-4-4-4-4-4-4-4
39	38' - 9.125"	4-4-4-4-4-4-4-4-3-3
40	39' - 9.125"	4-4-4-4-4-4-4-4-4-3-3
41	40' - 9.125"	4-4-4-4-4-4-4-4-4-3
42	41' - 9.125"	4-4-4-4-4-4-4-4-4-4
43	42' - 11.125"	4-4-4-4-4-4-4-4-4-3-3-3
44	43' - 11.125"	4-4-4-4-4-4-4-4-4-4-3-3
45	44' - 11.125"	4-4-4-4-4-4-4-4-4-4-3
46	45' - 11.125"	4-4-4-4-4-4-4-4-4-4-4
47	47' - 1.125"	4-4-4-4-4-4-4-4-4-3-3-3
48	48' - 1.125"	4-4-4-4-4-4-4-4-4-4-3-3
49	49' - 1.125"	4-4-4-4-4-4-4-4-4-4-4-3
50	50' - 1.125"	4-4-4-4-4-4-4-4-4-4-4-4

Number of Lamps

- 2' = (1) 2' lamp
- 3' = (1) 3' lamp
- 4' = (1) 4' lamp



#825-00092
V-0814