

# BRANDI

Wet Location Luminaire



# BRANDI Wet Location Luminaire



Compact yet thoroughly robust, BRANDI is designed for architectural applications which demand a performance-driven IP 65 rated, Wet-Location luminaire that can keep the toughest elements out, but hold the most sophisticated style in.

BRANDI's 2 3/4" mounting profile and concealed weather-sealing feature, comprise a luminaire designed to withstand wet outdoor conditions while still blending into the surrounding architecture with ease. Various mounting orientations make installations in hard-to-reach areas less harrowing and allow light delivered almost anywhere: outdoor entrances, under walkways or within structural eaves. Heavy gauge extruded aluminum housing, machined end caps, high impact extruded acrylic lenses in square or teardrop shapes with interior gasketing, make BRANDI the perfect choice under the most demanding weather conditions.

## Construction:

- Impact resistant flexible acrylic lens for durability & serviceability
- Square shaped or Teardrop shaped in either Frosted White acrylic, Polycarbonate White or Polycarbonate Clear

## Performance Optics:

- Frosted White symmetrical distribution

## Electrical:

- Custom User Specified Lumen & wattage output - available (CLO)
- Optional 1% dimming, emergency, dual circuit and sensors available
- UL & cUL listed for dry & damp locations

## PROFILE SIZES



275

## MOUNTING TYPES



Ceiling Mount



Wall Mount

## LENS APPLICATION TYPES



Tri Sided



Teardrop

## NOMINAL LENGTH



Standard  
2', 3', 4', 6' & 8'



Continuous Run (<8 Increments of 1')  
*(see matrix for segment lengths & cable spacing)*

## LENS/OPTIC TYPES

Efficacy:  
up to  
95lm/W  
Beam:  
105°



Frosted White  
(Standard)

\*See [specification sheet](#) for complete technical details.