



JAKE LED Wall Wash is a recessed linear luminaire comprised of various LED light source options that delivers high performing smooth illumination to the intended area and creating visual interest to the space. JAKE LED Wall Wash can be installed in gypsum ceilings or walls with either a 3/4" Trim (TR) or Trimless (TL) mud-over flange. T-grid models for drop ceilings are also available.

JAKE LED Light Outputs and dimmable driver components, when combined together, provide optimal LED lighting system capabilities. Optional Kicker Reflector (KR) delivers light to upper corners of wall/ceiling transitions to minimize shadowing.

Available in nominal lengths from 2' - 8' as well as continuous run.



Made in the USA



UL and c-UL listed for dry and damp locations.



Chicago Plenum



IC rated

FIXTURE SPECIFICATIONS

Construction

Fixture body is constructed of heavy gauge extruded aluminum. Fixtures are available in nominal lengths of 2 - 8 feet, and continuous run lengths.

Mounting

Recessed linear fixture for T-Grid ceiling installations. Available as continuous run mount. See installation information for specific details regarding installation guidelines. Various mounting clips available for ease of installation.

Finishes

Fixture exposed edges are standard Matte White (MW). Custom powder coat finishes available - consult factory.

LED Light Output System

LED Light Outputs are available as HLO (High Lumen Output) and SLO (Standard Lumen Output) providing efficient illumination. CLO (Custom Lumen Output) allows for end user specified lumen output or tailored wattage consumption for certain models. Consult factory for details.

Dimming

Dimming is available with a variety of control protocols and options. Consult factory for availability and specifications.

Custom and Mods

We proudly specialize in manufacturing custom and modified luminaires and have the ability to modify most of our standard fixtures. Please contact factory with any inquiries.

JAKE LED

3.50" Wall Wash
T-Grid

Type: Job Name:

Recessed Linear LED Fixture


SPECIFICATION CODE

JAK-LED-WW-350

model	trim style	light Output	color temp	length	voltage	driver	option	option
Model	Trim Style ²	Light Output	Color Temp	Nominal Length	Voltage	Driver	Options	
JAK-LED-WW-350	T-Grid Ceilings	SLO -	27 - 2700K	2 - 2'	120	D1 - 1% (nom) 0-10V	Finishes ²	
	LT9 - 9/16"	Standard	30 - 3000K	3 - 3'	277	HLA2 ³ -	CUP - Custom	
	exposed lay-in	Lumen Output	35 - 3500K	4 - 4'	347 ⁴	LTEA2W Lutron	powder coat	
	LT15 - 15/16"	HLO -	40 - 4000K	6 - 6'		H-Lume 1%, 2 wire		CP ⁵ - Chicago
	exposed lay-in	High		8 - 8'		HL -	Plenum	
	TT9 - 9/16" Tegular	Lumen Output				LDE1 Lutron		
	TT15 - 15/16" Tegular	CLO ⁴ -			CR ₁	Hi-Lume 1%		KR - Kicker
ITA - Interlude®	Custom			Continuous	EcoSystem		Reflector	
ST9 - Slot Grid	Lumen Output			Run	DALI - DALI			

[CLO Calculator](#)

Dimensions



NOTES

- 1 specify lengths in nominal feet
- 2 fixture exposed edges are standard Matte White see [option sheet](#) for custom finishes
- 3 120V only
- 4 available for D1, D10 drivers only
- 5 compliant with CCEA Chicago Plenum code requirements

Fixture Performance

JAK-LED-WW-350 (4000K)

SLO - 79.1 lm/watt delivered @ 4.4 w/ft fixture input watts, 348 lm/ft.

HLO - 74.4 lm/watt delivered @ 9 w/ft fixture input watts, 670 lm/ft.


CLO - refer to [CLO Calculator](#)

350 LED [supplement info](#)



Type: Job Name:

Recessed Linear LED Fixture


Photometrics



With Optional Kicker (KIC)




Fixture is mounted at 8' height and 2.0' from the wall




Fixture is mounted at 8' height and 3.0' from the wall

With Optional Kicker (KIC)



Fixture is mounted at 8' height and 2.0' from the wall



Fixture is mounted at 8' height and 3.0' from the wall

Gridscale = 1.0 ft per increment
Footcandle Legend

0.5 fc 1.0 fc 2.0 fc 5.0 fc 10.0 fc 20.0 fc

V-1016


Type:

Job Name:


Recessed Linear LED Fixture

T-GRID TRIM STYLES


ST9 - 9/16 SLOT GRID




ITA - Interlude




LT9 - 9/16 LAY-IN



TT9 - 9/16 TEGULAR



LT15 - 15/16 LAY-IN



TT15 - 15/16 TEGULAR

