



Offering show-stopping elegance within a dynamic geometric shape and profile, ERIKA creates a sensational impression in any interior application.

Horizontally cable-suspended, ERIKA's lean and modern design can be specified in either square or rectangular shapes of 1.25", 2.25" or 3.25" mitered extruded aluminum. Extruded frosted acrylic lenses in Flush, Reveal or Symmetrical Tri-side version, while integral dimming and battery pack options are also available for added lighting versatility.

Available with standard and custom lumen LED sources. Select Satin Clear (anodized), or Matte White or Flat Black (powder coat paint) as standard finishes. Custom finish options are also available.

ERI-125S



ERI-325S-TRI



ERI-325S-RLW



ERI-325S-FW

## FIXTURE SPECIFICATIONS

### Construction

Heavy gauge square extruded aluminum housing. Extruded acrylic lenses specifically engineered to maximize the performance and transmission from a variety of light sources.

### Mounting Options

Field-adjustable 1/8" aircraft (CSS) Cable Suspension System for use with bracket bar, 5" round canopy and cable gripper device. (CSS-M) Mono-point Cable Suspension System. 36" aircraft cable and (G) Gray power cord are included as standard. For horizontal mounting orientation only. (SM) Surface Mount for ceiling or wall.

### Finishes

(SC) Satin Clear anodize is standard finish. Other powder coat finishes available. Consult factory for options.

### LED Light Output System

LED Light Output is available as HLO (High Lumen Output) and SLO (Standard Lumen Output) providing efficient illumination. CLO (Custom Lumen Output) allows for end user specified lumen output or tailored wattage consumption for certain models.

### Dimming


Dimming is available with a variety of control protocols and options. Consult factory for availability and specifications.

### Acrylic Lens Style

(FW) Flush Frosted White lens, (RLW) Reveal Frosted White lens with 3/8" extension, (TRI) Tri-side Lens for all sizes.

### Custom and Mods

We proudly specialize in manufacturing custom and modified luminaires and have the ability to modify most of our standard fixtures. Please contact factory with any inquiries.

 UL and c-UL listed for dry and damp locations.

 Made in the USA

**SPECIFICATION CODE**

Css Selections Only

**ERI-LED-**

Model	Light Output	CCT/ CRI	Lens Style	Length	Finish	Voltage	Driver	Mounting	Options
<b>ERI-LED-125S</b> 1.25" Square Profile Fixture	<b>SLO</b> - Standard Lumen Output	<b>27</b> - 2700K/ 90 CRI <b>30</b> - 3000K/ 80 CRI <b>309</b> - 3000K/ 90 CRI	<b>FW</b> - Flush Lens Frosted White	Square <b>2X2</b> - 2' x 2' <b>3X3</b> - 3' x 3' <b>4X4</b> - 4' x 4'	Anodized <b>SC</b> - Satin Clear	<b>120</b> <b>277</b> <b>347</b> <sup>1</sup>	<b>D1</b> - 0-10V Dimming 1%	<b>SM</b> - Surface Mount	<b>CSS Options</b> Cable Length <sup>5</sup> Cord Color <sup>5</sup> Canopy <sup>5</sup> Canopy Finish <sup>5</sup>
<b>ERI-LED-225S-IB</b> 2.25" Square Profile Fixture, Integral Driver	<b>HLO</b> - High Lumen Output	<b>35</b> - 3500K/ 80 CRI <b>359</b> - 3500K/ 90 CRI <b>40</b> - 4000K/ 80 CRI <b>409</b> - 4000K/ 90 CRI	<b>RLW</b> - Reveal Frosted White 3/8" Extended	Rectangle <b>2X3</b> - 2' x 3' <b>2X4</b> - 2' x 4' <b>3X4</b> - 3' x 4'	Powder Coat <b>MW</b> - Matte White <b>FB</b> - Flat Black <b>CUP</b> - Custom <sup>3</sup>	<b>HLA2</b> <sup>4</sup> - LTRON Hi-Lume 2-Wire 1%  <b>HL</b> - LTRON Hi-Lume EcoSystem 1%	<b>HLA2</b> <sup>4</sup> - LTRON Hi-Lume 2-Wire 1%  <b>HL</b> - LTRON Hi-Lume EcoSystem 1%	<b>CSS</b> - Cable Suspended (36" Standard)  <b>CSS-M7</b> - Cable Suspended Mono Point	<b>CSS Options</b> Cable Length <sup>5</sup> Cord Color <sup>5</sup> Canopy <sup>5</sup> Canopy Finish <sup>5</sup>
<b>ERI-LED-225S-RB</b> <sup>6</sup> 2.25" Square Profile Fixture, Remote Driver	<b>CLO</b> <sup>1</sup> - Custom Lumen Output	<b>40</b> - 4000K/ 80 CRI <b>409</b> - 4000K/ 90 CRI	<b>TRI</b> - Tri-Side 1-1/2" Extended	Custom Size <sup>2</sup> __x__	<b>FB</b> - Flat Black <b>CUP</b> - Custom <sup>3</sup>	<b>HL</b> - LTRON Hi-Lume EcoSystem 1%	<b>HL</b> - LTRON Hi-Lume EcoSystem 1%	<b>CSS-M7</b> - Cable Suspended Mono Point	<b>CSS Options</b> Cable Length <sup>5</sup> Cord Color <sup>5</sup> Canopy <sup>5</sup> Canopy Finish <sup>5</sup>
<b>ERI-LED-325S</b> 3.25" Square Profile Fixture	<b>CLO</b> Calculator						<b>DALI</b> - DALI Dimming 1%		

**CSS Options**

Cable Length	Power Cord Color
<b>36</b> - 36" (Standard)	<b>W</b> - White
<b>72</b> - 72"	<b>B</b> - Black
<b>120</b> - 120"	<b>G</b> - Gray (Standard)
Canopy	Canopy Finish
<b>STND</b> - Bracket Bar w/ 5" Round Canopy	<b>MW</b> - Matte White (Standard) <b>SMT</b> - Silver Matte Texture <b>FB</b> - Flat Black <b>CUP</b> - Custom (Contact Factory)
<b>NC</b> - No Canopy 1/4-20 Side Exit Cable Gripper (1/4-20 Stud Provided By Others)	
<b>CU</b> - Custom (Contact Factory)	

**Notes**

1. Available for D1 & D10 drivers only
2. Contact factory for custom rectangle
3. Contact factory for custom finish
4. 120V only
5. See CSS options for non standard selections
6. Not available with tri lens style
7. Only available up to 4x4

**LED**

**125-FW (4000K FW lens)**

**SLO** - 95.5 lm/watt delivered @ 2.9 w/ft fixture input watts, 283 lm/ft.  
**HLO** - 95.0 lm/watt delivered @ 5.9 w/ft fixture input watts, 565 lm/ft.  
**CLO** - refer to [CLO Calculator](#)  
125 LED [supplement info](#)

**225-FW (4000K FW lens)**

**SLO** - 100.5 lm/watt delivered @ 2.9 w/ft fixture input watts, 292 lm/ft.  
**HLO** - 98.7 lm/watt delivered @ 5.9 w/ft fixture input watts, 583 lm/ft.  
**CLO** - refer to [CLO Calculator](#)  
225 LED [supplement info](#)

**225-TRI (4000K FW lens)**

**SLO** - 120.4 lm/watt delivered @ 2.9 w/ft fixture input watts, 349 lm/ft.  
**HLO** - 118.2 lm/watt delivered @ 5.9 w/ft fixture input watts, 698 lm/ft.  
**CLO** - refer to [CLO Calculator](#)  
225 LED [supplement info](#)

**325-FW (4000K FW lens)**

**SLO** - 90.8 lm/watt delivered @ 4.4 w/ft fixture input watts, 400 lm/ft.  
**HLO** - 85.4 lm/watt delivered @ 9 w/ft fixture input watts, 769 lm/ft.  
**CLO** - refer to [CLO Calculator](#)  
325 LED [supplement info](#)

**325-TRI (4000K FW lens)**

**SLO** - 111.4 lm/watt delivered @ 2.9 w/ft fixture input watts, 490 lm/ft.  
**HLO** - 104.7 lm/watt delivered @ 5.9 w/ft fixture input watts, 942 lm/ft.  
**CLO** - refer to [CLO Calculator](#)  
325 LED [supplement info](#)

**Dimensions**

